JAMBLINER QUOTE REQUEST WORKSHEET

Please complete all questions below:	NOTE: All Jambliners are Mad	de to Specifications and are I	Non-Returnable and Non-	-Cancelable	
1. Application Style (see Figure 1) (Check One):	☐ Bracket Type	☐ Flange Type			
2. Sash Style (see Figure 2) (Check One):	\square V Plough	☐ Square Plough			
3. Series (Check One):	☐ CB7200-Bracket-V Plough	CB7200-Bracket-Sq. Plough	☐ CB7200-Flange-V Plough	☐ CB7200-Flang	e-Sq. Plough
Series continued	☐ CB8500-Bracket-Double Hung	☐ CB8600-Flange-Double Hung	☐ CB8700-Bracket-Single Hu	ng	
4. Style (Check One):	\square Single Hung	☐ Double Hung		Bracket Type	Flange Type
5. Tilt/Non-Tilt (Check One):	□ Tilt	☐ Non-Tilt		.360	
6. Sash Thickness (Check One):	□ 1 ¼"	□ 1 ¾" □ 1 ¾′	,		
7. Sill Angle (Check One):	\square Square Cut	□ 15" □ Oth	er:		
8. Color (Check One):	\square White	☐ Beige			44
9. Visible Glass Height:	Top Sash:	Lower Sash:	FIGURE	1	
10. Visible Glass Weight:	Top Sash:	Lower Sash:			
11. Overall Length to the:	Longest Point:	Shortest Point:			4
Series CB7200	Series CB7	7200			F
3-3/8" 9/16" Bracket Type - V Plough 13/32" 13/32" 13/4" Flange Type - V Plough	9/16" 1" 3-3/8" 9/16" 3-3/8" 9/16" 3-3/8" 9/16" 1" 3-21/32"	1" 3/4"		square P 41/64" ries CB8700 //32" min opening	3/16"
Series CB8500 4-5/16" min. opening 35/64" 7/8" 1-5/16" Bracket Type Double Hung	1/32" 3/4" 1-5/16" 4-5/8	es CB8600 6" min. opening 5/8" 7/8" 7/8" arge Type	5	1-9/32"	25/32"
		ouble Hung	1-3	/4" Sash Only	Ray 1/8/20